

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
1228V255	3/4	28	26.1	0.50
1230V341	3/4	30	34.6	0.56
1230V348	3/4	30	35.3	0.50
1330V242	13/16	30	24.7	0.55
1422V215	7/8	22	22.0	0.50
1422V235	7/8	22	24.0	0.50
1422V240	7/8	22	24.7	0.55
1422V256	7/8	22	26.3	0.55
1422V270	7/8	22	27.5	0.55
1422V290	7/8	22	29.6	0.55
1422V300	7/8	22	30.7	0.55
1422V330	7/8	22	33.7	0.60
1422V340	7/8	22	34.6	0.75
1422V360	7/8	22	36.7	0.70
1422V400	7/8	22	40.8	0.65
1422V420	7/8	22	42.8	0.70
1422V440	7/8	22	44.5	0.70
1422V460	7/8	22	46.5	0.75
1422V466	7/8	22	47.0	0.75
1422V470	7/8	22	47.5	0.70
1422V480	7/8	22	48.7	0.75
1422V520	7/8	22	52.6	0.80
1422V540	7/8	22	54.8	0.90
1422V600	7/8	22	60.7	0.85
1422V660	7/8	22	66.7	0.92
1422V720	7/8	22	72.7	1.00

Part #	Top Width	Angle	Length	Weight (lbs)
1422V780	7/8	22	78.7	1.10
1426V298	7/8	26	30.4	0.70
1426V299	7/8	26	30.5	0.70
1426V328	7/8	26	33.3	0.75
1426V362	7/8	26	36.7	0.78
1430V215	7/8	30	21.8	0.50
1430V315	7/8	30	32.0	0.60
1430V375	7/8	30	38.0	0.47
1430V450	7/8	30	45.6	0.77
1430V500	7/8	30	50.5	0.80
1522V270	15/16	22	27.5	0.70
1524V301	15/16	24	30.6	0.63
1526V294	15/16	26	30.0	0.65
1528V298	15/16	28	30.3	0.62
1528V326	15/16	28	33.1	0.61
1528V360	15/16	28	36.5	0.70
1528V414	15/16	28	41.9	0.79
1622V270	1	22	27.5	0.60
1622V297	1	22	30.2	0.65
1622V307	1	22	31.1	0.65
1622V336	1	22	34.1	0.65
1622V520	1	22	52.5	0.85
1626V218	1	26	22.3	0.50
1626V262	1	26	26.7	0.56
1626V290	1	26	29.8	0.75
1626V293	1	26	30.0	0.75

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24	28	V	345
24/16" or 1 1/2"			345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
1626V339	1	26	34.7	0.74
1626V356	1	26	36.1	0.60
1626V380	1	26	38.5	0.74
1626V384	1	26	39.2	0.80
1626V395	1	26	40.3	0.85
1626V411	1	26	41.9	0.85
1626V428	1	26	43.3	0.80
1626V440	1	26	44.7	1.05
1626V455	1	26	46.2	0.80
1626V513	1	26	51.8	0.40
1626V517	1	26	52.1	1.10
1626V597	1	26	60.6	0.95
1626V604	1	26	61.2	1.30
1626V653	1	26	66.2	1.15
1626V658	1	26	66.7	1.18
1626V661	1	26	66.9	1.20
1626V700	1	26	70.8	1.30
1628V210	1	28	21.2	0.75
1628V315	1	28	32.7	0.75
1632V210	1	32	21.9	0.75
1632V220	1	32	22.5	0.80
1632V250	1	32	25.5	0.85
1822V207	1-1/8	22	21.0	0.60
1822V290	1-1/8	22	29.5	0.65

Part #	Top Width	Angle	Length	Weight (lbs)
1822V551	1-1/8	22	55.9	0.95
1822V590	1-1/8	22	59.9	0.95
1822V629	1-1/8	22	63.0	1.15
1826V250	1-1/8	26	25.4	0.55
1828V368	1-1/8	28	37.6	0.90
1832V338	1-1/8	32	34.4	0.80
1922V250	1-3/16	22	25.5	0.75
1922V256	1-3/16	22	26.4	0.80
1922V277	1-3/16	22	28.2	0.80
1922V282	1-3/16	22	29.0	0.80
1922V292	1-3/16	22	29.7	0.80
1922V298	1-3/16	22	30.6	0.85
1922V300	1-3/16	22	30.7	0.85
1922V302	1-3/16	22	30.8	0.85
1922V321	1-3/16	22	33.0	0.85
1922V332	1-3/16	22	34.0	0.95
1922V333	1-3/16	22	34.1	0.95
1922V338	1-3/16	22	34.7	0.95
1922V363	1-3/16	22	37.1	0.95
1922V381	1-3/16	22	38.8	1.00
1922V386	1-3/16	22	39.3	1.05
1922V390	1-3/16	22	39.6	0.90
1922V403	1-3/16	22	41.4	0.95
1922V408	1-3/16	22	41.9	1.00

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
1922V417	1-3/16	22	42.5	1.00
1922V420	1-3/16	22	42.8	1.00
1922V426	1-3/16	22	43.4	1.10
1922V433	1-3/16	22	44.0	1.10
1922V443	1-3/16	22	45.1	1.25
1922V454	1-3/16	22	46.2	1.25
1922V460	1-3/16	22	46.8	1.25
1922V481	1-3/16	22	49.1	1.25
1922V484	1-3/16	22	49.2	1.25
1922V526	1-3/16	22	53.3	1.25
1922V544	1-3/16	22	55.1	1.30
1922V554	1-3/16	22	56.2	1.30
1922V604	1-3/16	22	61.2	1.50
1922V630	1-3/16	22	63.6	1.20
1922V646	1-3/16	22	65.4	1.34
1922V651	1-3/16	22	65.9	1.45
1922V666	1-3/16	22	67.4	1.60
1922V686	1-3/16	22	69.3	1.68
1922V706	1-3/16	22	71.3	1.76
1922V721	1-3/16	22	72.7	1.70
1922V726	1-3/16	22	73.0	1.80
1922V751	1-3/16	22	75.8	1.74
1922V756	1-3/16	22	76.4	1.70
1922V806	1-3/16	22	81.3	1.80
1922V846	1-3/16	22	85.4	1.87
1922V891	1-3/16	22	89.7	1.80

Part #	Top Width	Angle	Length	Weight (lbs)
1922V966	1-3/16	22	97.2	1.90
1922V1006	1-3/16	22	101.3	2.36
1922V1026	1-3/16	22	103.2	2.73
1922V1146	1-3/16	22	115.4	3.25
1922V1260	1-3/16	22	127.0	3.50
1926V249	1-3/16	26	25.3	0.60
1926V250	1-3/16	26	25.7	0.65
1926V275	1-3/16	26	28.1	0.65
1926V333	1-3/16	26	33.9	0.95
1926V367	1-3/16	26	37.2	0.95
1926V376	1-3/16	26	38.8	0.85
1926V380	1-3/16	26	38.9	1.00
1926V390	1-3/16	26	39.6	1.00
1926V407	1-3/16	26	41.4	1.05
1926V415	1-3/16	26	42.1	1.10
1926V427	1-3/16	26	40.3	1.10
1926V507	1-3/16	26	51.4	1.20
1926V542	1-3/16	26	55.4	1.34
1930V215	1-3/16	30	22.0	0.80
1930V355	1-3/16	30	36.1	0.90
1930V366	1-3/16	30	37.2	1.00
1930V375	1-3/16	30	38.1	0.94
1930V400	1-3/16	30	40.7	1.00
1930V425	1-3/16	30	43.1	1.10
1930V431	1-3/16	30	44.0	1.20
1930V450	1-3/16	30	45.6	1.00

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24	28	V	345
24/16" or 1 1/2"			345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
1930V485	1-3/16	30	49.1	1.26
1930V491	1-3/16	30	50.0	1.25
1930V500	1-3/16	30	50.6	1.20
1930V530	1-3/16	30	53.6	1.20
1930V541	1-3/16	30	55.0	1.45
1930V560	1-3/16	30	56.9	1.25
1930V585	1-3/16	30	59.1	1.33
1930V591	1-3/16	30	60.0	1.18
1930V600	1-3/16	30	60.6	1.21
1930V630	1-3/16	30	63.6	1.36
1930V641	1-3/16	30	64.6	1.43
1930V670	1-3/16	30	67.7	1.60
1930V691	1-3/16	30	69.6	1.55
1930V710	1-3/16	30	71.7	1.60
1930V750	1-3/16	30	75.6	1.68
1930V791	1-3/16	30	79.6	1.76
1930V800	1-3/16	30	80.6	1.50
1930V850	1-3/16	30	85.6	1.57
1930V891	1-3/16	30	89.6	1.96
1930V900	1-3/16	30	90.6	2.11
1930V950	1-3/16	30	95.6	1.78
1930V991	1-3/16	30	99.6	2.14
1930V1000	1-3/16	30	101.2	2.23
1930V1060	1-3/16	30	106.6	2.08
1930V1091	1-3/16	30	109.6	2.81

Part #	Top Width	Angle	Length	Weight (lbs)
1930V1191	1-3/16	30	119.6	2.54
1934V371	1-3/16	34	37.7	1.00
2026V422	1-1/4	26	43.0	0.95
2026V445	1-1/4	26	45.2	1.05
2026V474	1-1/4	26	48.2	1.52
2026V607	1-1/4	26	61.5	1.20
2026V645	1-1/4	26	65.4	1.50
2028V315	1-1/4	28	32.2	1.00
2028V447	1-1/4	28	45.2	0.90
2030V381	1-1/4	30	38.5	0.80
2032V624	1-1/4	32	63.2	1.00
2042V1035	1-1/4	42	104.5	2.80
2126V297	1-5/16	26	30.4	0.85
2126V307	1-5/16	26	31.4	0.85
2126V309	1-5/16	26	31.7	0.90
2126V365	1-5/16	26	37.4	1.05
2126V377	1-5/16	26	38.4	1.05
2126V468	1-5/16	26	47.7	1.35
2130V374	1-5/16	30	38.0	1.10
2226V276	1-3/8	26	28.3	0.80
2226V307	1-3/8	26	31.2	0.85
2230V266	1-3/8	30	27.5	0.80
2230V270	1-3/8	30	27.7	0.80
2230V273	1-3/8	30	27.9	0.80
2230V275	1-3/8	30	28.1	0.80

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
2230V285	1-3/8	30	29.3	0.85
2230V326	1-3/8	30	33.5	0.85
2230V345	1-3/8	30	35.3	0.85
2230V375	1-3/8	30	38.2	1.15
2230V422	1-3/8	30	42.7	1.15
2230V890	1-3/8	30	90.0	1.80
2322V329	1-7/16	22	33.4	1.15
2322V347	1-7/16	22	35.2	1.05
2322V364	1-7/16	22	37.2	1.05
2322V372	1-7/16	22	37.9	1.10
2322V373	1-7/16	22	38.0	1.10
2322V384	1-7/16	22	39.3	1.10
2322V396	1-7/16	22	40.6	1.30
2322V421	1-7/16	22	42.9	1.35
2322V434	1-7/16	22	44.2	1.30
2322V441	1-7/16	22	45.1	1.40
2322V461	1-7/16	22	47.0	1.50
2322V481	1-7/16	22	49.2	1.55
2322V486	1-7/16	22	49.4	1.55
2322V491	1-7/16	22	49.8	1.55
2322V521	1-7/16	22	52.8	1.55
2322V541	1-7/16	22	55.1	1.60
2322V544	1-7/16	22	55.1	1.60
2322V601	1-7/16	22	61.2	1.75
2322V604	1-7/16	22	61.2	1.90
2322V621	1-7/16	22	63.0	1.90

Part #	Top Width	Angle	Length	Weight (lbs)
2322V661	1-7/16	22	67.4	2.15
2322V667	1-7/16	22	68.0	2.15
2322V681	1-7/16	22	68.8	2.15
2322V701	1-7/16	22	71.4	2.15
2322V721	1-7/16	22	73.4	2.15
2322V723	1-7/16	22	73.6	2.25
2322V801	1-7/16	22	81.4	2.45
2322V826	1-7/16	22	83.3	2.60
2322V846	1-7/16	22	85.3	2.67
2322V886	1-7/16	22	89.5	2.63
2322V921	1-7/16	22	92.8	3.00
2322V964	1-7/16	22	97.2	3.15
2322V1001	1-7/16	22	101.4	3.15
2322V1061	1-7/16	22	106.8	3.70
2322V1271	1-7/16	22	127.9	3.75
2326V310	1-7/16	26	31.8	0.93
2326V359	1-7/16	26	36.6	1.10
2328V345	1-7/16	28	35.2	1.10
2330V273	1-7/16	30	27.9	0.80
2330V338	1-7/16	30	34.6	1.05
2330V359	1-7/16	30	36.5	1.15
2330V537	1-7/16	30	54.6	1.55
2332V373	1-7/16	32	38.0	1.10
2422V570	1-1/2	22	57.7	1.85
2426V343	1-1/2	26	35.4	1.33
2428V345	1-1/2	28	35.2	1.20

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
2428V707	1-1/2	28	71.5	3.10
2428V757	1-1/2	28	76.6	2.85
2428V806	1-1/2	28	81.4	3.50
2428V807	1-1/2	28	81.5	3.50
2430V297	1-1/2	30	30.7	1.00
2430V302	1-1/2	30	30.9	1.00
2430V319	1-1/2	30	32.6	1.00
2430V345	1-1/2	30	35.2	1.10
2430V354	1-1/2	30	36.3	1.10
2430V364	1-1/2	30	37.2	1.10
2430V379	1-1/2	30	38.6	1.50
2430V388	1-1/2	36	39.5	1.50
2436V331	1-1/2	36	34.0	1.00
2436V333	1-1/2	36	34.2	1.00
2526V302	1-9/16	26	30.7	1.05
2526V314	1-9/16	26	32.4	1.30
2528V370	1-9/16	28	37.7	1.40
2530V300	1-9/16	30	31.0	1.12
2530V309	1-9/16	30	31.9	1.15
2530V335	1-9/16	30	34.2	1.20
2530V434	1-9/16	30	44.1	1.25
2530V470	1-9/16	30	47.7	1.65
2530V490	1-9/16	30	50.0	2.00
2530V500	1-9/16	30	50.9	3.00
2530V530	1-9/16	30	54.0	3.25
2530V550	1-9/16	30	56.0	3.30

Part #	Top Width	Angle	Length	Weight (lbs)
2530V560	1-9/16	30	56.7	3.30
2530V575	1-9/16	30	58.5	3.30
2530V595	1-9/16	30	60.7	3.50
2530V600	1-9/16	30	60.7	3.50
2530V610	1-9/16	30	62.0	3.50
2530V618	1-9/16	30	62.5	3.50
2530V630	1-9/16	30	64.2	3.80
2530V660	1-9/16	30	67.0	3.90
2530V670	1-9/16	30	68.2	4.00
2530V675	1-9/16	30	68.4	4.05
2530V680	1-9/16	30	68.7	4.05
2530V690	1-9/16	30	70.0	4.10
2530V700	1-9/16	30	71.0	4.15
2530V710	1-9/16	30	72.0	4.15
2530V730	1-9/16	30	74.2	4.25
2530V740	1-9/16	30	75.0	4.35
2530V750	1-9/16	30	76.2	4.40
2530V790	1-9/16	30	80.0	4.60
2530V800	1-9/16	30	81.0	4.70
2530V840	1-9/16	30	85.0	4.75
2530V850	1-9/16	30	85.7	4.80
2530V890	1-9/16	30	90.0	4.98
2530V900	1-9/16	30	91.0	5.00
2530V934	1-9/16	30	94.4	5.20
2530V950	1-9/16	30	96.0	5.50
2530V990	1-9/16	30	100.0	5.50

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
2530V1090	1-9/16	30	110.0	5.87
2530V1187	1-9/16	30	119.3	6.00
2530V1190	1-9/16	30	119.7	6.30
2530V1250	1-9/16	30	126.0	6.30
2530V1290	1-9/16	30	130.0	6.73
2530V1490	1-9/16	30	150.0	6.75
2530V1690	1-9/16	30	169.8	6.80
2626V293	1-5/8	26	30.3	1.60
2626V369	1-5/8	26	37.4	1.64
2626V388	1-5/8	26	39.7	1.65
2626V428	1-5/8	26	43.8	1.70
2630V345	1-5/8	30	35.3	1.33
2630V395	1-5/8	30	40.2	1.50
2636V332	1-5/8	36	34.0	1.41
2822V778	1-3/4	22	79.5	5.48
2826V412	1-3/4	26	41.9	1.99
2826V452	1-3/4	26	46.0	2.92
2830V337	1-3/4	30	34.8	1.68
2830V363	1-3/4	30	36.8	1.47
2830V366	1-3/4	30	37.2	1.07
2830V367	1-3/4	30	37.9	1.80
2830V387	1-3/4	30	39.6	1.30
2830V393	1-3/4	30	39.9	1.38
2830V396	1-3/4	30	40.3	1.28
2830V422	1-3/4	30	42.7	1.46
2830V428	1-3/4	30	43.6	1.88

Part #	Top Width	Angle	Length	Weight (lbs)
2830V492	1-3/4	30	50.1	1.85
2830V567	1-3/4	30	57.6	2.00
2830V646	1-3/4	30	65.5	2.25
2830V666	1-3/4	30	67.5	2.25
2836V300	1-3/4	36	30.5	1.60
2836V343	1-3/4	36	35.1	1.69
2836V350	1-3/4	36	35.8	1.72
2836V361	1-3/4	36	37.0	1.50
2836V380	1-3/4	36	38.8	1.84
2926V348	1-13/16	26	35.6	1.50
2926V366	1-13/16	26	37.5	1.57
2926V400	1-13/16	26	40.8	1.85
2926V426	1-13/16	26	43.5	2.11
2926V452	1-13/16	26	46.0	2.20
2926V456	1-13/16	26	46.4	2.25
2926V471	1-13/16	26	48.0	3.08
2926V477	1-13/16	26	48.5	2.45
2926V486	1-13/16	26	49.2	2.39
2926V491	1-13/16	26	50.0	3.17
2926V521	1-13/16	26	53.0	3.30
2926V534	1-13/16	26	54.2	2.29
2926V546	1-13/16	26	55.5	3.38
2926V574	1-13/16	26	58.3	3.52
2926V586	1-13/16	26	59.5	3.55
2926V606	1-13/16	26	61.5	3.66
2926V613	1-13/16	26	63.2	3.70

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
2926V776	1-13/16	26	78.5	4.38
2926V786	1-13/16	26	79.4	4.44
2926V834	1-13/16	26	84.2	4.64
2926V856	1-13/16	26	86.4	4.77
2926V891	1-13/16	26	90.0	3.92
2926V906	1-13/16	26	91.5	4.96
2926V921	1-13/16	26	93.0	4.30
2926V966	1-13/16	26	97.5	5.20
2926V1006	1-13/16	26	101.5	5.39
2926V1026	1-13/16	26	103.6	5.46
2926V1086	1-13/16	26	109.6	5.76
2926V1106	1-13/16	26	111.6	6.00
2926V1146	1-13/16	26	115.6	6.20
2926V1276	1-13/16	26	128.8	6.50
2930V348	1-13/16	26	35.5	2.00
2930V420	1-13/16	26	42.9	2.50
2930V492	1-13/16	26	50.0	3.14
3028V386	1-7/8	28	39.4	2.00
3030V357	1-7/8	30	36.5	1.88
3030V377	1-7/8	30	38.7	1.50
3030V387	1-7/8	30	39.6	2.02
3036V351	1-7/8	36	36.0	1.79
3226V392	2	26	39.8	2.21
3226V395	2	26	40.4	2.00
3226V400	2	26	41.1	2.28
3226V433	2	26	44.1	1.95

Part #	Top Width	Angle	Length	Weight (lbs)
3226V434	2	26	44.2	2.00
2926V616	1-13/16	26	63.3	3.75
2926V636	1-13/16	26	64.4	3.79
2926V646	1-13/16	26	65.5	3.81
2926V666	1-13/16	26	67.5	4.16
2926V686	1-13/16	26	69.5	4.00
2926V706	1-13/16	26	71.5	4.10
2926V726	1-13/16	26	73.5	4.17
2926V750	1-13/16	26	75.9	3.40
3226V439	2	26	44.7	2.14
3226V450	2	26	45.8	2.72
3226V465	2	26	47.4	2.98
3226V505	2	26	51.4	3.15
3226V514	2	26	52.3	2.87
3226V545	2	26	55.3	2.57
3226V585	2	26	59.4	3.48
3226V603	2	26	61.4	4.18
3226V650	2	26	65.9	3.50
3226V663	2	26	67.4	3.80
3226V690	2	26	69.8	3.50
3226V723	2	26	73.4	4.05
3226V783	2	26	79.5	5.11
3226V834	2	26	84.5	5.20
3226V843	2	26	85.4	5.25
3226V903	2	26	91.4	5.30
3226V963	2	26	97.4	5.35

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
3226V973	2	26	98.4	5.50
3226V1023	2	26	103.4	5.50
3226V1083	2	26	109.4	5.60
3230HV553	2	30	56.3	3.60
3230HV570	2	30	58.0	3.60
3230HV585	2	30	59.5	3.70
3230HV603	2	30	61.3	3.80
3230HV613	2	30	62.3	3.90
3230HV620	2	30	63.0	4.00
3230HV626	2	30	63.6	4.10
3230HV644	2	30	65.4	4.10
3230HV670	2	30	68.0	4.30
3230HV685	2	30	69.5	4.30
3230HV702	2	30	71.2	4.40
3230HV723	2	30	73.3	4.50
3230HV821	2	30	83.1	4.90
3230HV856	2	30	86.7	6.44
3230HV931	2	30	94.2	7.01
3230HV960	2	30	97.0	5.40
3230HV1060	2	30	107.3	6.00
3230V1120	2	30	112.8	5.50
3230V1180	2	30	118.8	6.72
3230V1250	2	30	126.0	7.20
3230V419	2	30	42.7	3.06
3230V481	2	30	48.9	3.15
3230V528	2	30	53.7	3.25

Part #	Top Width	Angle	Length	Weight (lbs)
3230V553	2	30	56.3	3.50
3230V560	2	30	56.8	3.50
3230V585	2	30	59.5	3.50
3230V600	2	30	61.0	3.60
3230V613	2	30	62.3	3.65
3230V630	2	30	63.8	3.65
3230V644	2	30	65.2	3.75
3230V670	2	30	67.8	3.85
3230V690	2	30	69.8	3.90
3230V701	2	30	70.9	3.95
3230V710	2	30	72.0	3.95
3230V750	2	30	76.0	4.00
3230V771	2	30	78.1	4.20
3230V800	2	30	81.0	4.25
3230V821	2	30	83.0	4.25
3230V850	2	30	85.8	4.30
3230V871	2	30	87.9	4.90
3230V900	2	30	91.0	5.20
3230V950	2	30	96.0	5.50
3236HV528	2	36	53.8	3.58
3236HV553	2	36	56.3	4.48
3236HV570	2	36	58.0	4.59
3236HV585	2	36	59.5	3.70
3236HV603	2	36	61.3	4.79
3236HV613	2	36	62.2	4.83
3236HV620	2	36	63.0	4.91

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
3236HV626	2	36	63.6	4.93
3236HV644	2	36	65.4	5.06
3236HV670	2	36	68.0	5.22
3236HV702	2	36	71.1	5.44
3236HV723	2	36	73.2	5.57
3236HV821	2	36	83.1	6.14
3236V342	2	36	35.1	1.50
3236V369	2	36	37.7	2.07
3236V389	2	36	39.7	2.17
3236V432	2	36	44.2	2.39
3236V552	2	36	56.2	2.50
3236V584	2	36	59.2	2.60
3236V643	2	36	65.4	2.65
3236V903	2	36	91.5	2.70
3326V478	2-1/16	26	48.5	2.77
3428V451	2-1/8	28	46.0	2.43
3430V424	2-1/8	30	43.3	2.35
3430V450	2-1/8	30	46.0	2.10
3430V456	2-1/8	30	46.6	2.10
3430V476	2-1/8	30	48.8	3.23
3430V480	2-1/8	30	49.0	2.20
3430V484	2-1/8	30	49.6	2.25
3430V493	2-1/8	30	50.1	2.80
3430V510	2-1/8	30	52.2	2.90
3432V450	2-1/8	32	45.8	2.45
3432V456	2-1/8	32	46.5	2.50

Part #	Top Width	Angle	Length	Weight (lbs)
3432V480	2-1/8	32	48.8	2.65
3432V484	2-1/8	32	49.3	2.45
3432V528	2-1/8	32	53.4	2.85
3432V534	2-1/8	32	54.3	2.85
3436V404	2-1/8	36	41.3	3.00
3626V556	2-1/4	26	56.5	4.82
3630V455	2-1/4	30	46.4	2.75
3636V479	2-1/4	36	48.8	3.87
3726V558	2-5/16	26	56.9	5.39
3826V459	2-3/8	26	46.8	2.80
3826V465	2-3/8	26	47.5	4.06
3830V501	2-3/8	30	51.0	4.50
3830V510	2-3/8	30	52.0	4.68
3830V515	2-3/8	30	52.5	4.70
3830V517	2-3/8	30	52.7	4.36
3830V580	2-3/8	30	59.0	5.18
3830V587	2-3/8	30	59.6	4.13
3836V418	2-3/8	36	42.7	3.67
3836V426	2-3/8	36	43.6	3.01
3836V654	2-3/8	36	66.3	4.29
3836V734	2-3/8	36	74.4	4.30
3836V794	2-3/8	36	80.4	4.50
3836V795	2-3/8	36	80.5	2.90
4030V538	2-1/2	30	54.5	3.30
4030V590	2-1/2	30	60.0	4.15
4034V1000	2-1/2	34	101.1	10.00

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
4036V541	2-1/2	36	55.4	5.28
4036V574	2-1/2	36	58.3	5.02
4230V503	2-5/8	30	51.4	5.25
4230V526	2-5/8	30	53.7	5.25
4230V556	2-5/8	30	56.8	5.30
4230V605	2-5/8	30	61.6	5.24
4230V653	2-5/8	30	66.5	4.50
4234V998	2-5/8	34	100.9	10.73
4330V521	2-11/16	30	53.2	5.72
4430V730	2-3/4	30	74.0	7.31
4430V740	2-3/4	30	75.0	7.36
4430V750	2-3/4	30	76.0	8.17
4430V760	2-3/4	30	77.0	6.77
4430V767	2-3/4	30	77.8	6.60
4430V772	2-3/4	30	78.6	10.59
4430V780	2-3/4	30	79.0	6.50
4430V790	2-3/4	30	80.0	7.81
4430V800	2-3/4	30	81.0	7.85
4430V850	2-3/4	30	86.0	8.31
4430V900	2-3/4	30	91.0	8.50
4430V910	2-3/4	30	92.0	8.81
4430V930	2-3/4	30	94.1	9.00
4430V950	2-3/4	30	96.1	9.30
4430V970	2-3/4	30	98.0	9.35
4430V1000	2-3/4	30	101.1	10.24
4430V1030	2-3/4	30	104.0	9.81

Part #	Top Width	Angle	Length	Weight (lbs)
4430V1060	2-3/4	30	107.2	9.20
4430V1090	2-3/4	30	110.0	10.31
4430V1120	2-3/4	30	113.0	13.00
4430V1150	2-3/4	30	116.0	13.22
4430V1180	2-3/4	30	119.1	10.00
4430V1250	2-3/4	30	126.1	12.51
4430V1320	2-3/4	30	133.0	12.28
4430V1410	2-3/4	30	142.0	13.53
4430V1460	2-3/4	30	147.0	13.97
4430V1610	2-3/4	30	162.0	15.28
4430V1810	2-3/4	30	182.0	17.04
4430V1917	2-3/4	30	192.7	17.98
4430V455	2-3/4	30	46.5	5.40
4430V510	2-3/4	30	52.0	5.48
4430V530	2-3/4	30	54.0	5.60
4430V548	2-3/4	30	55.9	5.75
4430V555	2-3/4	30	56.5	5.81
4430V560	2-3/4	30	57.0	4.63
4430V570	2-3/4	30	58.0	5.10
4430V578	2-3/4	30	59.0	6.04
4430V600	2-3/4	30	61.0	4.97
4430V610	2-3/4	30	62.0	6.31
4430V630	2-3/4	30	64.0	6.45
4430V652	2-3/4	30	66.2	5.78
4430V660	2-3/4	30	67.0	6.70
4430V670	2-3/4	30	68.0	6.81

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

Top Width	Intended pulley angle	Variable Speed	Length
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

Part #	Top Width	Angle	Length	Weight (lbs)
4430V690	2-3/4	30	70.0	6.95
4430V700	2-3/4	30	71.0	7.06
4430V710	2-3/4	30	72.1	6.54
4430V718	2-3/4	30	72.8	7.88
4436V329	2-3/4	36	33.8	5.50
4436V525	2-3/4	36	53.5	5.56
4436V551	2-3/4	36	56.1	5.70
4436V555	2-3/4	36	56.5	5.81
4436V561	2-3/4	36	57.1	4.65
4436V576	2-3/4	36	58.6	5.99
4436V581	2-3/4	36	59.1	4.81
4436V646	2-3/4	36	65.5	6.55
4436V714	2-3/4	36	72.7	8.48
4436V750	2-3/4	36	76.1	7.80
4626V596	2-7/8	26	60.6	6.91
4630V650	2-7/8	30	66.1	8.40
4630V663	2-7/8	30	67.3	8.49
4630V668	2-7/8	30	68.1	9.47
4630V683	2-7/8	30	69.3	8.76
4630V733	2-7/8	30	74.3	9.83
4630V756	2-7/8	30	76.7	7.60
4630V1070	2-7/8	30	108.1	11.49
4632V659	2-7/8	32	67.0	7.00
4632V680	2-7/8	32	69.0	7.50
4632V722	2-7/8	32	73.5	9.00
4636V612	2-7/8	36	62.1	7.00

Part #	Top Width	Angle	Length	Weight (lbs)
4636V613	2-7/8	36	62.2	7.01
4830V602	3	30	61.1	7.61
4830V614	3	30	62.5	7.23
4830V653	3	30	66.4	7.61
4830V683	3	30	69.4	7.70
4830V692	3	30	70.3	7.99
4830V699	3	30	71.0	8.06
4830V730	3	30	74.1	8.44
4830V750	3	30	76.0	8.55
4830V850	3	30	86.1	9.55
4830V970	3	30	98.1	10.73
4830V1000	3	30	101.1	11.00
4830V1070	3	30	108.1	11.63
4836V588	3	36	59.8	6.88
4836V608	3	36	61.9	7.05
4836V618	3	36	63.4	7.22
4836V642	3	36	65.3	7.41
4836V655	3	36	66.6	7.54
4836V659	3	36	67.0	7.75
4836V670	3	36	68.4	6.40
4836V700	3	36	71.4	6.60
4836V710	3	36	72.4	6.50
4836V729	3	36	74.0	8.00
4836V750	3	36	76.4	8.25
4836V789	3	36	80.0	9.00
4836V800	3	36	81.1	9.30

"Variable Speed Belt" Section



Michigan Industrial Belting Inc.

31617 Glendale St.

Livonia, MI 48150

1-800-778-1650

www.mibelting.com

Explanation of Part Number

<i>Top Width</i>	<i>Intended pulley angle</i>	<i>Variable Speed</i>	<i>Length</i>
24 24/16" or 1 1/2"	28	V	345 345/10" or 34.5"

We have years of experience & service under our belts

<i>Part #</i>	<i>Top Width</i>	<i>Angle</i>	<i>Length</i>	<i>Weight (lbs)</i>
4836V850	3	36	86.1	9.49
4836V900	3	36	91.4	7.60
4836V950	3	36	96.4	8.50
4836V1000	3	36	101.4	9.00
4836V1060	3	36	107.4	9.75
4836V1120	3	36	113.4	10.00
4836V1180	3	36	119.3	13.00
4836V1250	3	36	126.4	13.25
5126V938	3-3/16	26	95.0	11.65
5130V732	3-3/16	30	74.6	10.87
5130V787	3-3/16	30	80.0	26.00
5228V930	3-1/4	28	94.4	26.49
5230V652	3-1/4	30	66.6	9.00
5230V662	3-1/4	30	67.3	9.35
5230V734	3-1/4	30	75.3	20.47
5230V867	3-1/4	30	88.3	22.56
5230V928	3-1/4	30	94.4	23.00
5428V959	3-3/8	28	97.5	23.50
5430V783	3-3/8	30	80.0	24.00
5636V750	3-1/2	36	76.4	12.39

<i>Part #</i>	<i>Top Width</i>	<i>Angle</i>	<i>Length</i>	<i>Weight (lbs)</i>
5636V774	3-1/2	36	78.7	12.75
5636V845	3-1/2	36	85.8	13.00
5830V737	3-5/8	30	75.0	13.50
5830V756	3-5/8	30	76.9	13.60
5836V737	3-5/8	36	75.0	13.50
6036V761	3-3/4	36	77.7	14.70
6036V850	3-3/4	36	86.3	13.28
6136V751	3-4/5	36	76.6	12.40
6136V756	3-4/5	36	77.2	13.60
6236V607	3-7/8	36	62.1	10.75
6236V694	3-7/8	36	70.8	11.21
6236V725	3-7/8	36	73.9	12.58
6236V762	3-7/8	36	77.6	13.19
6236V785	3-7/8	36	79.9	12.15
6236V849	3-7/8	36	86.3	14.00
6236V905	3-7/8	36	91.9	14.38
6236V969	3-7/8	36	98.3	15.00
6236V1009	3-7/8	36	102.2	15.50
6236V1321	3-7/8	36	133.5	16.00