Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB10

Catalog #	**10**
Item number:	**10402**

Description:
3 Ply Poly 105 White Teflon FDA COS

International Designation:
N/A

Construction:

Compound Top Cover	White Teflon
Color	White
Top Cover Thickness (in)	(0.05 mm) 0.00 in
Top Cover Description	Teflon
Compound Bottom Cover	White Nitrile
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	3
Overall Gauge (in)	(1.59 mm) 1/16 in
Unit Weight- lb/PIW	0.0500 lbs/PIW
Carcass Type	Polyester
Compound	White Nitrile
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.50 in

Belt Strength:

Tension Rating (PIW)	105 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#62
Clipper Lace	#1XSP
Alligator Lace	#1

Special Characteristics:

Excellent for wet, sticky materials and operations involving gluing, coating, spreading; best release characteristics. The slippery top surface is created by the thin teflon film. Carcass is strong and flexible. FDA accepted.

*****All Values are nominal and subject to change without notice.*****