



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

We have years of experience and service under our belts.

MIB100

Catalog #	100
Item number:	10930
Description:	PVC 450 Blk C x C SC/FR
International Designation:	N/A

Pulley Diameter, Minimum:	
Minimum Pulley Diameter Conveyor	10.00 in
Minimum Pulley Diameter Elevator	14.00 in

Bucket Projection, Maximum:	
Maximum Bucket Projection Grain	9.00 in
Maximum Bucket Projection Industrial	9.00 in

Construction:	
Compound Top Cover	Black PVC
Color	Black
Top Cover Description	Smooth
Compound Bottom Cover	Black PVC
Bottom Cover Description	Smooth
Number of Plies	1
Overall Gauge (in)	(7.94 mm) 5/16 in
Unit Weight- lb/PIW	0.1940 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	Black PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Belt Strength:	
Tension Rating Conveyor (PIW)	450 PIW
Tension Rating Elevator (PIW) Allowable	450 PIW
Tension Rating Elevator (PIW) Preferred	350 PIW

Other:	
Static Conducting	Yes
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	Yes
FDA Approved	No

Suggested Fasteners:	
Flexco Plate/Rivet	R5
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:
 The most common, best performance yield elevator belting available in the feed and grain industry. Features low stretch; trouble-free operation; high bolt-holding ability; and resistance to grain oils. Also static conductive and flame resistant. Dura-Splice and Maxi-Splice recommended for bucket elevator applications.

*****All Values are nominal and subject to change without notice.*****