Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB100a

Catalog #	**100a**
Item number:	**41992**

Description:
PVC 600 Blk C x C SC/FR

International Designation:
N/A

Construction:

Compound Top Cover	Black PVC
Color	Black
Top Cover Description	Smooth
Compound Bottom Cover	Black PVC
Bottom Cover Description	Smooth
Number of Plies	1
Overall Gauge (in)	(9.53 mm) 3/8 in
Unit Weight- lb/PIW	0.2000 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	Black PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum:

Minimum Pulley Diameter Conveyor	12.00 in
Minimum Pulley Diameter Elevator	16.00 in

Bucket Projection, Maximum:

Maximum Bucket Projection Grain	11.00 in
Maximum Bucket Projection Industrial	10.00 in

Belt Strength:

Tension Rating Conveyor (PIW)	600 PIW
Tension Rating Elevator (PIW) Allowable	600 PIW
Tension Rating Elevator (PIW) Preferred	450 PIW

Other:

Static Conducting	Yes
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	Yes
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	R5
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

The most common, best performance yield elevator belting available in the feed and grain industry. Features low stretch; trouble-free operation; high bolt-holding ability; and resistance to grain oils. Also static conductive and flame resistant. Dura-Splice and Maxi-Splice recommended for bucket elevator applications.

*****All Values are nominal and subject to change without notice.*****