Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB-11

Catalog # 11
Item number: 10384
Description:
2 Ply Poly 60 White Nitrile Pebbletop
International Designation:
N/A

Construction:

Compound Top Cover	White Nitrile
Color	White
Top Cover Thickness (in)	(0.79 mm) 1/32 in
Top Cover Description	Pebbletop
Compound Bottom Cover	White Nitrile
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	2
Overall Gauge (in)	(2.38 mm) 3/32 in
Unit Weight- lb/PIW	0.0500 lbs/PIW
Carcass Type	Polyester
Compound	White Nitrile
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.00 in

Belt Strength:

Tension Rating (PIW)	60 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#62
Clipper Lace	#1A
Alligator Lace	#7

Special Characteristics:

The cover features a textured pattern (known as Tyler Wire Impression) that is capable of high traction on moderate inclines. Suitable for conveying produce, bakery goods, packages and small parts. Oil and grease resistant, non-marking. FDA accepted.

*****All Values are nominal and subject to change without notice.*****