Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB118HAL

Catalog #	**118HAL**
Item number:	**50244**

Description:
2 Ply Poly CR80 Green RMV LG x FS

International Designation:
E14/2 U0/RMV11 LR Green AS

Construction:

Compound Top Cover	Rubber Modified Vinyl (RMV)
Top Cover Thickness (in)	(1.10 mm) 0.0433 in
Top Cover Description	Longitudinally Grooved
Top Cover Shore	35A
Compound Bottom Cover	PU Impregnated
Bottom Cover Thickness (in)	(0.00 mm) 0.0000 in
Bottom Cover Description	PU Impregnated
Bottom Cover Shore	N/A
Number of Plies	2
Anti Static	Yes
Overall Gauge (in)	(2.50 mm) 0.0984 in
Unit Weight- lb/PIW	0.0000 lbs/PIW
Material Between Plies	N/A
Maximum Width (in)	78 in
Temperature Range (°F)- High	150 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum



A) Normal Flex	(50.80 mm) 2.0000 in
B) Back Flex	(66.04 mm) 2.6000 in

Belt Strength:

Pull for 1% Elongation	(14 N/mm) 80 lbs/sq in

Splice Instructions:

Foil	No
Splice Process	Finger
Press Temperature (°F)	350 °F
Press Pressure (psi)	18 lbs/sq in

Note: Listed above is a guideline only. Every vulcanizer is different and will show different results. We recommend that you do a test splice with your press before attempting the actual belt splice.

Other:

Cross Rigid	Yes
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Special Characteristics:

#118 HAL features a high friction longitudinally ribbed cover surface designed to handle packages on incline conveyors. The cover compound will also maintain its grip in wet conditions.

*****All Values are nominal and subject to change without notice.*****