



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

We have years of experience and service under our belts.

MIB140a

Catalog #	140a
Item number:	10556
Description:	3 Ply 330 1/8in x 1/16in Cleat Top MOR
International Designation:	N/A

Pulley Diameter, Minimum	
Min. Pulley Dia. - Head @ 80 - 100% Tension	18.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	16.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	12.00 in
Minimum Pulley Diameter- Tail	12.00 in

Construction:	
Compound Top Cover	Black MOR
Color	Black
Top Cover Thickness (in)	(3.30 mm) 1/8 in
Top Cover Description	Cleated
Compound Bottom Cover	Black MOR
Bottom Cover Thickness (in)	(1.60 mm) 1/16 in
Bottom Cover Description	Smooth
Number of Plies	3
Overall Gauge (in)	(9.14 mm) 23/64 in
Unit Weight- lb/PIW	0.2650 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black MOR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Splice Instructions:	
Splice Step Size	8.00 in
Splice Process	Step Hot

Other:	
Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Belt Strength:	
Tension Rating (PIW)	330 PIW

Suggested Fasteners:	
Flexco Plate/Rivet	#190/R5
Flexco Hinged	#550
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

Made to prevent or reduce slideback on steep inclines. Chevron belting also increases conveyor capacity by quick pick-up at the point of loading. Ideal for wet and/or granular materials such as wet sand and gravel.

NOTE: OAG DOES NOT INCLUDE THE CLEAT HEIGHT

*****All Values are nominal and subject to change without notice.*****