



# Michigan Industrial Belting Inc.

31617 Glendale St.  
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

*We have years of experience and service under our belts.*

## MIB140c

<b>Catalog #</b>	<b>140c</b>
<b>Item number:</b>	<b>10566</b>
<b>Description:</b>	3 Ply 330 1/8in x Bare Cleat Top MOR
<b>International Designation:</b>	N/A

<b>Pulley Diameter, Minimum</b>	
Min. Pulley Dia. - Head @ 80 - 100% Tension	18.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	16.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	12.00 in
Minimum Pulley Diameter- Tail	12.00 in

<b>Construction:</b>	
Compound Top Cover	Black MOR
Color	Black
Top Cover Thickness (in)	(3.30 mm) 1/8 in
Top Cover Description	Cleated
Compound Bottom Cover	Bare RFL
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	3
Overall Gauge (in)	(10.16 mm) 25/64 in
Unit Weight- lb/PIW	0.2150 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black MOR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

<b>Splice Instructions:</b>	
Splice Step Size	8.00 in
Splice Process	Step Hot

<b>Other:</b>	
Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

<b>Belt Strength:</b>	
Tension Rating (PIW)	330 PIW

<b>Suggested Fasteners:</b>	
Flexco Plate/Rivet	#190/R5
Flexco Hinged	#550
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

**Special Characteristics:**

Made to prevent or reduce slideback on steep inclines. Chevron belting also increases conveyor capacity by quick pick-up at the point of loading. Ideal for slider bed applications, handling wet and/or granular materials such as wet sand and gravel. Also popular in recycling and wood chip applications.

\*\*\*NOTE: OAG DOES NOT INCLUDE THE CLEAT HEIGHT\*\*\*

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*