Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

# MIB16-4

**Catalog #** 16-4
**Item number:** 10342
**Description:**
4 Ply Solid Woven Cotton
**International Designation:**
N/A

**Construction:**

| | |
|---|---|
| Compound Top Cover | White Cotton Fabric |
| Color | White |
| Top Cover Thickness (in) | (0.00 mm) 0.00 in |
| Top Cover Description | Untreated |
| Compound Bottom Cover | White Cotton Fabric |
| Bottom Cover Thickness (in) | (0.00 mm) 0.00 in |
| Bottom Cover Description | Untreated |
| Number of Plies | 4 |
| Overall Gauge (in) | (4.76 mm) 3/16 in |
| Unit Weight- lb/PIW | 0.0560 lbs/PIW |
| Carcass Type | Cotton |
| Compound | White Cotton Fabric |
| Temperature Range (°F)- High | 225 °F |
| Temperature Range (°F)- Low | -40 °F |

**Pulley Diameter, Minimum**

| | |
|---|---|
| Minimum Pulley Diameter | 3.00 in |

**Belt Strength:**

| | |
|---|---|
| Tension Rating (PIW) | 110 PIW |

**Splice Instructions:**

| | |
|---|---|
| Splice Step | No |
| Splice Finger | No |

**Other:**

| | |
|---|---|
| Static Conducting | No |
| Cross Rigid | No |
| High Heat | No |
| Impression Top | No |
| Oil Resistant | No |
| Fire Resistant | No |
| FDA Approved | Yes |

**Suggested Fasteners:**

| | |
|---|---|
| Flexco Plate/Rivet | N/A |
| Flexco Hinged | N/A |
| Alligator Staple | N/A |
| Clipper Lace | #3 |
| Alligator Lace | #20 |

**Special Characteristics:**

Still a popular conveyor belting, particularly in the food and baking industries. Economical answer to many light and medium conveying needs, especially slider bed applications. The belt is firmly woven; non-rubberized. Number of stripes usually indicates the number of plies. Also can be used as an air-permeable fabric designed for pneumatic conveyors.

*****All Values are nominal and subject to change without notice.*****