Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB16a

Catalog # 16a
Item number: 10208
Description:
Polyveyor 0.5 CFM Rated #1950
International Designation:
N/A

Construction:

Compound Top Cover	None
Color	White
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	Calendared
Compound Bottom Cover	None
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Calendared
Number of Plies	1
Overall Gauge (in)	(6.35 mm) 1/4 in
Unit Weight- lb/PIW	0.0600 lbs/PIW
Carcass Type	Needled Polyester
Compound	None
Temperature Range (°F)- High	310 °F
Temperature Range (°F)- Low	-60 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	0.00 in

Belt Strength:

Tension Rating (PIW)	60 PIW

Splice Instructions:

Splice Step	No
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

Designed specifically for air gravity conveyors. Used to fluidize dry bulk powders such as: cement, barite, silica, alumina, etc.. Provides several advantages over woven air permeable fabrics because it does not require stretching prior to installation and will not unravel when cut or punched.

*****All Values are nominal and subject to change without notice.*****