Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB91W

Catalog # **20**
Item number: **10957**
Description:
PVC 120 White C x FS OR/FDA
International Designation:
N/A

Construction:

Compound Top Cover	White PVC
Color	White
Top Cover Description	Smooth
Compound Bottom Cover	White PVC
Bottom Cover Description	Friction Surface
Number of Plies	1
Overall Gauge (in)	(3.57 mm) 9/64 in
Unit Weight- lb/PIW	0.0690 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	White PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.00 in

Belt Strength:

Tension Rating (PIW)	120 PIW

Splice Instructions:

Splice Step	No
Splice Finger	Yes

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#2
Alligator Lace	#15

Special Characteristics:

This PVC belt offers the highest service yield and is the best value for most food processing uses. It features a smooth, easy-clean OFR cover of PVC compounds that is oil & fat resistant. FDA accepted.

*****All Values are nominal and subject to change without notice.*****