



# Michigan Industrial Belting Inc.

31617 Glendale St.  
Livonia, MI 48150

*We have years of experience and service under our belts.*

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

## MIB21

<b>Catalog #</b>	<b>21</b>
<b>Item number:</b>	<b>10950</b>
<b>Description:</b>	PVC 150 White C x FS OR/FDA
<b>International Designation:</b>	N/A

<b>Pulley Diameter, Minimum</b>	
Minimum Pulley Diameter	3.00 in

<b>Belt Strength:</b>	
Tension Rating (PIW)	150 PIW

<b>Construction:</b>	
Compound Top Cover	White PVC
Color	White
Top Cover Description	Smooth
Compound Bottom Cover	Woven Poly
Bottom Cover Description	Friction Surface
Number of Plies	1
Overall Gauge (in)	(4.01 mm) 5/32 in
Unit Weight- lb/PIW	0.0750 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	White PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

<b>Splice Instructions:</b>	
Splice Step	No
Splice Finger	Yes

<b>Other:</b>	
Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

<b>Suggested Fasteners:</b>	
Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#2
Alligator Lace	#15

**Special Characteristics:**

This PVC belt offers the highest service yield and is the best value for most food processing uses. It features a smooth, easy-clean cover of PVC compounds that is oil resistant. FDA accepted.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*