Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB22

Catalog # 22
Item number: 10953
Description:
PVC 100 White Roughtop x FS OR FDA
International Designation:
N/A

Construction:

Compound Top Cover	White PVC
Color	White
Top Cover Description	Roughtop
Compound Bottom Cover	Woven Poly
Bottom Cover Description	Friction Surface
Number of Plies	1
Overall Gauge (in)	(6.75 mm) 17/64 in
Unit Weight- lb/PIW	0.0940 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	White PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.50 in

Belt Strength:

Tension Rating (PIW)	100 PIW

Splice Instructions:

Splice Step	No
Splice Finger	Yes

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#7

Special Characteristics:

Rough-textured surface enables packages, boxes, cases and other products to be conveyed on incline or decline. FDA accepted

*****All Values are nominal and subject to change without notice.*****