Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB28

Catalog #	**28**
Item number:	**10708**

Description:
5 Ply Poly 225 Blk Heavy Duty Nitrile FBS

International Designation:
N/A

Construction:

Compound Top Cover	Polyester
Color	Black
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	Friction Surface
Compound Bottom Cover	Polyester
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	5
Overall Gauge (in)	(4.37 mm) 11/64 in
Unit Weight- lb/PIW	0.0940 lbs/PIW
Carcass Type	Polyester
Compound	Black Nitrile
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	3.00 in

Belt Strength:

Tension Rating (PIW)	225 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	#3
Alligator Lace	#20

Special Characteristics:

These belts are recommended for handling metal stampings, automotive parts, sheet steel and any application requiring very high oil resistance. Features rugged, high-strength polyester carcass; suitable for medium-capacity transmission belt where oil, grease or chemicals are present. Flexible, yet will withstand cutting, gouging and abrasion.

*****All Values are nominal and subject to change without notice.*****