Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB30

Catalog # 30
Item number: 10698
Description:
3 Ply Poly 135 Blk Nitrile COS
International Designation:
N/A

Construction:

Compound Top Cover	Black Nitrile
Color	Black
Top Cover Thickness (in)	(1.19 mm) 3/64 in
Top Cover Description	Smooth
Compound Bottom Cover	Black Nitrile
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	3
Overall Gauge (in)	(3.57 mm) 9/64 in
Unit Weight- lb/PIW	0.0750 lbs/PIW
Carcass Type	Polyester
Compound	Black Nitrile
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.50 in

Belt Strength:

Tension Rating (PIW)	135 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#15

Special Characteristics:

All-purpose conveyor belt with smooth nitrile top covers for assembly line, packaging and a wide variety of industrial uses. Flexible, yet strong, the 3 ply features a heavier polyester carcass for added stretch resistance. This belt has superior oil, grease and animal fat resistance and good heat capability. FDA approved.

*****All Values are nominal and subject to change without notice.*****