Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788

We have years of experience and service under our belts.

Est 1978

MIB45

Catalog #	**45**
Item number:	**10894**

Description:
8 Ply 35oz Tan FS x FS Silver Hard Duck

International Designation:
N/A

Construction:

Compound Top Cover	Tan SBR
Color	Tan
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	Friction Surface
Compound Bottom Cover	Tan SBR
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	8
Overall Gauge (in)	(12.70 mm) 1/2 in
Unit Weight- lb/PIW	0.2130 lbs/PIW
Carcass Type	35oz Silver Hard Duck
Compound	Tan SBR
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	-40 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	16.00 in

Belt Strength:

Tension Rating (PIW)	280 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	R5
Flexco Hinged	#550
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

Constructed of rugged silver hard duck fabric plies with heavy skim coats between and friction surface both sides. This belt is formulated for severe conditions and rugged service. Excellent fastener-holding ability. Can be spliced endless or with a mechanical fastener.

*****All Values are nominal and subject to change without notice.*****