



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

We have years of experience and service under our belts.

MIB46

Catalog #	46
Item number:	10580
Description:	3 Ply Hot Stock and Water
International Designation:	N/A

Pulley Diameter, Minimum	
Minimum Pulley Diameter	2.50 in

Belt Strength:	
Tension Rating (PIW)	90 PIW

Construction:	
Compound Top Cover	White Bare Duck
Color	White
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	White Bare Duck
Compound Bottom Cover	Black SBR
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	3
Overall Gauge (in)	(3.57 mm) 9/64 in
Unit Weight- lb/PIW	0.0560 lbs/PIW
Carcass Type	Cotton-Polyester
Compound	Black SBR
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	-40 °F

Splice Instructions:	
Splice Step	Yes
Splice Finger	No

Other:	
Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:	
Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#2
Alligator Lace	#15

Special Characteristics:
Bare duck surface down for lowest possible friction for slider bed use, and up for deflector bar applications; ideal as slip-top belt for "stall" operations. Its true use is for conveying uncured rubber in tire plants.

*****All Values are nominal and subject to change without notice.*****