Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB51

Catalog # 51
Item number: 10462
Description:
2 Ply 220 Tan Bare x Bare
International Designation:
N/A

Construction:

Compound Top Cover	Poly/Nylon
Color	Tan
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	Bare
Compound Bottom Cover	Poly/Nylon
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	2
Overall Gauge (in)	(3.97 mm) 5/32 in
Unit Weight- lb/PIW	0.0690 lbs/PIW
Carcass Type	Polyester
Compound	Black SBR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	8.00 in

Belt Strength:

Tension Rating (PIW)	220 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	R2
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	N/A
Alligator Lace	#15

Special Characteristics:

This belt features a high-strength 2 ply polyester-nylon carcass. It is ideal for applications requiring a low coefficient of friction on both the top and bottom.

*****All Values are nominal and subject to change without notice.*****