Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB53a

Catalog # **53a**
Item number: **10882**
Description:
4 Ply 180 Black 3/32in Smooth Nitrile Top x Bare
International Designation:
N/A

Construction:

Compound Top Cover	Black Nitrile
Color	Black
Top Cover Thickness (in)	(2.29 mm) 5/64 in
Top Cover Description	Smooth
Compound Bottom Cover	Poly/Nylon
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	4
Overall Gauge (in)	(6.35 mm) 1/4 in
Unit Weight- lb/PIW	0.1300 lbs/PIW
Carcass Type	Polyester
Compound	Black Nitrile
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	4.00 in

Belt Strength:

Tension Rating (PIW)	180 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#187
Clipper Lace	#5
Alligator Lace	#25

Special Characteristics:

This is a smooth top belt used for the wood sander and metal finishing industries. Abuse-resistant nitrile top cover makes this belt ideal for oily cut and gouge applications.

*****All Values are nominal and subject to change without notice.*****