



# Michigan Industrial Belting Inc.

31617 Glendale St.  
Livonia, MI 48150

*We have years of experience and service under our belts.*

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

## MIB53c

<p><b>Catalog #</b>                   <b>53c</b></p> <p><b>Item number:</b>               <b>10448</b></p> <p><b>Description:</b> 2 Ply 220 3/16in x Bare MOR</p> <p><b>International Designation:</b> N/A</p>	<p><b>Pulley Diameter, Minimum</b></p> <p>Min. Pulley Dia. - Head @ 80 - 100% Tension                   14.00 in</p> <p>Min. Pulley Dia. - Head @ 60 - 79% Tension                   12.00 in</p> <p>Min. Pulley Dia. - Head @ 59% Tension or Below               10.00 in</p> <p>Minimum Pulley Diameter- Tail                                       10.00 in</p>
<p><b>Construction:</b></p> <p>Compound Top Cover   Black MOR</p> <p>Color   Black</p> <p>Top Cover Thickness (in)   (4.76 mm) 3/16 in</p> <p>Top Cover Description   Smooth</p> <p>Compound Bottom Cover   Polyester</p> <p>Bottom Cover Thickness (in)   (0.00 mm) 0.00 in</p> <p>Bottom Cover Description   Bare</p> <p>Number of Plies   2</p> <p>Overall Gauge (in)   (7.37 mm) 9/32 in</p> <p>Unit Weight- lb/PIW   0.1700 lbs/PIW</p> <p>Carcass Type   Poly/Nylon</p> <p>Compound   Black MOR</p> <p>Temperature Range (°F)- High   225 °F</p> <p>Temperature Range (°F)- Low   -25 °F</p>	<p><b>Splice Instructions:</b></p> <p>Splice Step Size   8.00 in</p> <p>Splice Process   Step Hot</p>
<p><b>Belt Strength:</b></p> <p>Tension Rating (PIW)   220 PIW</p>	<p><b>Other:</b></p> <p>Static Conducting   No</p> <p>Cross Rigid   No</p> <p>High Heat   No</p> <p>Impression Top   No</p> <p>Oil Resistant   Yes</p> <p>Fire Resistant   No</p> <p>FDA Approved    No</p>
<p><b>Special Characteristics:</b></p> <p>This belt is designed for medium-duty uses. Ideal for slider bed applications. It features a MOR compound for applications where some oil or wood terpenes are present.</p>	
<p>*****All Values are nominal and subject to change without notice.*****</p>	