Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB54

Catalog # 54
Item number: 10602
Description:
2 Ply 150 Black Roughtop x Bare
International Designation:
N/A

Construction:

Compound Top Cover	Black SBR
Color	Black
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	Roughtop
Compound Bottom Cover	Bare RFL
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	2
Overall Gauge (in)	(7.14 mm) 9/32 in
Unit Weight- lb/PIW	0.1000 lbs/PIW
Carcass Type	Polyester
Compound	Black SBR
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	-40 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.00 in

Belt Strength:

Tension Rating (PIW)	150 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#1

Special Characteristics:

Construction is two plies of high-strength, all-synthetic polyester fabrics. Very flexible, low stretch and moisture resistant incline/decline belt.

*****All Values are nominal and subject to change without notice.*****