Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB57

Catalog #	**57**
Item number:	**10680**
Description:	
4 Ply CP30 Black Roughtop x FS	
International Designation:	
N/A	

Construction:

Compound Top Cover	Black SBR
Color	Black
Top Cover Thickness (in)	(0.00 mm) 0.00 in
Top Cover Description	Roughtop
Compound Bottom Cover	Black SBR
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	4
Overall Gauge (in)	(10.32 mm) 13/32 in
Unit Weight- lb/PIW	0.1100 lbs/PIW
Carcass Type	Cotton-Polyester
Compound	Black SBR
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	-40 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	4.00 in

Belt Strength:

Tension Rating (PIW)	112 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#15

Special Characteristics:

Long a popular standard in the industry. The cotton/polyester blend carcass gives a hefty appearance and cushioning effect.

*****All Values are nominal and subject to change without notice.*****