



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

We have years of experience and service under our belts.

Catalog #	MIB-60c
Item number:	10630
Description:	3 Ply 150 Brown Butyl Roughtop x Bare
International Designation:	N/A

Pulley Diameter, Minimum	
Minimum Pulley Diameter	2.50 in

Belt Strength:	
Tension Rating (PIW)	150 PIW

Construction:	
Compound Top Cover	Butyl/EPDM
Color	Brown
Top Cover Thickness (in)	(3.30 mm) 1/8 in
Top Cover Description	Roughtop
Compound Bottom Cover	Bare RFL
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	3
Overall Gauge (in)	(7.62 mm) 19/64 in
Unit Weight- lb/PIW	0.1000 lbs/PIW
Carcass Type	Polyester
Compound	Butyl/EPDM
Temperature Range (°F)- High	300 °F
Temperature Range (°F)- Low	-65 °F

Splice Instructions:	
Splice Step	Yes
Splice Finger	No

Other:	
Static Conducting	No
Cross Rigid	No
High Heat	Yes
Impression Top	Yes
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:	
Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#1

Special Characteristics:
The Butyl properties of this belt provide good resistance to heat, chemicals, abrasion and is an excellent option for shock absorption.

*****All Values are nominal and subject to change without notice.*****