Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB7

Catalog # 7
Item number: 10385
Description:
2 Ply Poly 100 White Nitrile FDA COS
International Designation:
N/A

Construction:

Compound Top Cover	White Nitrile
Color	White
Top Cover Thickness (in)	(1.19 mm) 3/64 in
Top Cover Description	Smooth
Compound Bottom Cover	White Nitrile
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Friction Surface
Number of Plies	2
Overall Gauge (in)	(2.78 mm) 7/64 in
Unit Weight- lb/PIW	0.0620 lbs/PIW
Carcass Type	RFL Polyester
Compound	White Nitrile
Temperature Range (°F)- High	250 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.00 in

Belt Strength:

Tension Rating (PIW)	100 PIW

Splice Instructions:

Splice Step	Yes
Splice Finger	No

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	Yes

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	#1A
Alligator Lace	#7

Special Characteristics:

Thicker, stronger version of the Poly White Nitrile Series; features heavier, stronger polyester fabric RFL treated for greater adhesion under rugged conditions; also heavier skim coats between plies and a superior wear-resistant nitrile cover; usual advantages of 100% polyester carcass. Can be hot water and steam cleaned. FDA approved.

*****All Values are nominal and subject to change without notice.*****