



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

We have years of experience and service under our belts.

MIB-70

<p>Catalog # MIB 70</p> <p>Item number: 10406</p> <p>Description: 2 Ply 150 1/32in x 1/32in</p> <p>International Designation: N/A</p>	<p>Pulley Diameter, Minimum</p> <p>Min. Pulley Dia. - Head @ 80 - 100% Tension 6.00 in</p> <p>Min. Pulley Dia. - Head @ 60 - 79% Tension 6.00 in</p> <p>Min. Pulley Dia. - Head @ 59% Tension or Below 6.00 in</p> <p>Minimum Pulley Diameter- Tail 6.00 in</p>
<p>Construction:</p> <p>Compound Top Cover Black SBR</p> <p>Color Black</p> <p>Top Cover Thickness (in) (0.80 mm) 1/32 in</p> <p>Top Cover Description Smooth</p> <p>Compound Bottom Cover Black SBR</p> <p>Bottom Cover Thickness (in) (0.80 mm) 1/32 in</p> <p>Bottom Cover Description Smooth</p> <p>Number of Plies 2</p> <p>Overall Gauge (in) (3.97 mm) 5/32 in</p> <p>Unit Weight- lb/PIW 0.1010 lbs/PIW</p> <p>Carcass Type Poly/Nylon</p> <p>Compound Black SBR</p> <p>Temperature Range (°F)- High 225 °F</p> <p>Temperature Range (°F)- Low -25 °F</p>	<p>Splice Instructions:</p> <p>Splice Step Size 8.00 in</p> <p>Splice Process Step Hot</p>
<p>Belt Strength:</p> <p>Tension Rating (PIW) 150 PIW</p>	<p>Other:</p> <p>Static Conducting No</p> <p>Cross Rigid No</p> <p>High Heat No</p> <p>Impression Top No</p> <p>Oil Resistant No</p> <p>Fire Resistant No</p> <p>FDA Approved No</p>
<p>Suggested Fasteners:</p> <p>Flexco Plate/Rivet N/A</p> <p>Flexco Hinged N/A</p> <p>Alligator Staple #125</p> <p>Clipper Lace N/A</p> <p>Alligator Lace N/A</p>	

Special Characteristics:

This belt is compounded to provide excellent abrasion resistance and flex life and is the best buy for the majority of conveyor belt applications. Its high-tension synthetic fabrics result in minimum stretch, great fastener holding ability, impact resistance and the highest adhesion between plies and cover.

*****All Values are nominal and subject to change without notice.*****