



# Michigan Industrial Belting Inc.

31617 Glendale St.  
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

*We have years of experience and service under our belts.*

## MIB-73

<b>Catalog #</b>	<b>73</b>
<b>Item number:</b>	<b>10426</b>
<b>Description:</b>	2 Ply 220 1/8in x 1/16in
<b>International Designation:</b>	N/A

<b>Pulley Diameter, Minimum</b>	
Min. Pulley Dia. - Head @ 80 - 100% Tension	16.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	14.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	10.00 in
Minimum Pulley Diameter- Tail	10.00 in

<b>Construction:</b>	
Compound Top Cover	Black SBR
Color	Black
Top Cover Thickness (in)	(3.30 mm) 1/8 in
Top Cover Description	Smooth
Compound Bottom Cover	Black SBR
Bottom Cover Thickness (in)	(1.60 mm) 1/16 in
Bottom Cover Description	Smooth
Number of Plies	2
Overall Gauge (in)	(7.87 mm) 19/64 in
Unit Weight- lb/PIW	0.1660 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black SBR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

<b>Splice Instructions:</b>	
Splice Step Size	8.00 in
Splice Process	Step Hot

<b>Other:</b>	
Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

<b>Belt Strength:</b>	
Tension Rating (PIW)	220 PIW

<b>Suggested Fasteners:</b>	
Flexco Plate/Rivet	#140/R5
Flexco Hinged	#375 or 550
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

**Special Characteristics:**  
 This belt is compounded to provide excellent abrasion resistance and flex life and is the best buy for the majority of conveyor belt applications. Its high-tension synthetic fabrics result in minimum stretch, great fastener holding ability, impact resistance and the highest adhesion between plies and cover.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*