



# Michigan Industrial Belting Inc.

31617 Glendale St.  
Livonia, MI 48150

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

*We have years of experience and service under our belts.*

## MIB75b

<p><b>Catalog #</b>                    <b>75b</b></p> <p><b>Item number:</b>                <b>10444</b></p> <p><b>Description:</b> 2 Ply 220 3/16in x 1/16in MOR</p> <p><b>International Designation:</b> N/A</p>	<p><b>Pulley Diameter, Minimum</b></p> <table border="0"> <tr> <td>Min. Pulley Dia. - Head @ 80 - 100% Tension</td> <td>16.00 in</td> </tr> <tr> <td>Min. Pulley Dia. - Head @ 60 - 79% Tension</td> <td>14.00 in</td> </tr> <tr> <td>Min. Pulley Dia. - Head @ 59% Tension or Below</td> <td>10.00 in</td> </tr> <tr> <td>Minimum Pulley Diameter- Tail</td> <td>10.00 in</td> </tr> </table>	Min. Pulley Dia. - Head @ 80 - 100% Tension	16.00 in	Min. Pulley Dia. - Head @ 60 - 79% Tension	14.00 in	Min. Pulley Dia. - Head @ 59% Tension or Below	10.00 in	Minimum Pulley Diameter- Tail	10.00 in																								
Min. Pulley Dia. - Head @ 80 - 100% Tension	16.00 in																																
Min. Pulley Dia. - Head @ 60 - 79% Tension	14.00 in																																
Min. Pulley Dia. - Head @ 59% Tension or Below	10.00 in																																
Minimum Pulley Diameter- Tail	10.00 in																																
<p><b>Construction:</b></p> <table border="0"> <tr> <td>Compound Top Cover</td> <td>Black MOR</td> </tr> <tr> <td>Color</td> <td>Black</td> </tr> <tr> <td>Top Cover Thickness (in)</td> <td>(4.83 mm) 3/16 in</td> </tr> <tr> <td>Top Cover Description</td> <td>Smooth</td> </tr> <tr> <td>Compound Bottom Cover</td> <td>Black MOR</td> </tr> <tr> <td>Bottom Cover Thickness (in)</td> <td>(1.60 mm) 1/16 in</td> </tr> <tr> <td>Bottom Cover Description</td> <td>Smooth</td> </tr> <tr> <td>Number of Plies</td> <td>2</td> </tr> <tr> <td>Overall Gauge (in)</td> <td>(8.73 mm) 11/32 in</td> </tr> <tr> <td>Unit Weight- lb/PIW</td> <td>0.1810 lbs/PIW</td> </tr> <tr> <td>Carcass Type</td> <td>Poly/Nylon</td> </tr> <tr> <td>Compound</td> <td>Black MOR</td> </tr> <tr> <td>Temperature Range (°F)- High</td> <td>225 °F</td> </tr> <tr> <td>Temperature Range (°F)- Low</td> <td>-25 °F</td> </tr> </table>	Compound Top Cover	Black MOR	Color	Black	Top Cover Thickness (in)	(4.83 mm) 3/16 in	Top Cover Description	Smooth	Compound Bottom Cover	Black MOR	Bottom Cover Thickness (in)	(1.60 mm) 1/16 in	Bottom Cover Description	Smooth	Number of Plies	2	Overall Gauge (in)	(8.73 mm) 11/32 in	Unit Weight- lb/PIW	0.1810 lbs/PIW	Carcass Type	Poly/Nylon	Compound	Black MOR	Temperature Range (°F)- High	225 °F	Temperature Range (°F)- Low	-25 °F	<p><b>Splice Instructions:</b></p> <table border="0"> <tr> <td>Splice Step Size</td> <td>8.00 in</td> </tr> <tr> <td>Splice Process</td> <td>Step Hot</td> </tr> </table>	Splice Step Size	8.00 in	Splice Process	Step Hot
Compound Top Cover	Black MOR																																
Color	Black																																
Top Cover Thickness (in)	(4.83 mm) 3/16 in																																
Top Cover Description	Smooth																																
Compound Bottom Cover	Black MOR																																
Bottom Cover Thickness (in)	(1.60 mm) 1/16 in																																
Bottom Cover Description	Smooth																																
Number of Plies	2																																
Overall Gauge (in)	(8.73 mm) 11/32 in																																
Unit Weight- lb/PIW	0.1810 lbs/PIW																																
Carcass Type	Poly/Nylon																																
Compound	Black MOR																																
Temperature Range (°F)- High	225 °F																																
Temperature Range (°F)- Low	-25 °F																																
Splice Step Size	8.00 in																																
Splice Process	Step Hot																																
<p><b>Belt Strength:</b></p> <table border="0"> <tr> <td>Tension Rating (PIW)</td> <td>220 PIW</td> </tr> </table>	Tension Rating (PIW)	220 PIW	<p><b>Other:</b></p> <table border="0"> <tr> <td>Static Conducting</td> <td>No</td> </tr> <tr> <td>Cross Rigid</td> <td>No</td> </tr> <tr> <td>High Heat</td> <td>No</td> </tr> <tr> <td>Impression Top</td> <td>No</td> </tr> <tr> <td>Oil Resistant</td> <td>Yes</td> </tr> <tr> <td>Fire Resistant</td> <td>No</td> </tr> <tr> <td>FDA Approved</td> <td>No</td> </tr> </table>	Static Conducting	No	Cross Rigid	No	High Heat	No	Impression Top	No	Oil Resistant	Yes	Fire Resistant	No	FDA Approved	No																
Tension Rating (PIW)	220 PIW																																
Static Conducting	No																																
Cross Rigid	No																																
High Heat	No																																
Impression Top	No																																
Oil Resistant	Yes																																
Fire Resistant	No																																
FDA Approved	No																																
<p><b>Suggested Fasteners:</b></p> <table border="0"> <tr> <td>Flexco Plate/Rivet</td> <td>#140/R5</td> </tr> <tr> <td>Flexco Hinged</td> <td>#375 or 550</td> </tr> <tr> <td>Alligator Staple</td> <td>N/A</td> </tr> <tr> <td>Clipper Lace</td> <td>N/A</td> </tr> <tr> <td>Alligator Lace</td> <td>N/A</td> </tr> </table>		Flexco Plate/Rivet	#140/R5	Flexco Hinged	#375 or 550	Alligator Staple	N/A	Clipper Lace	N/A	Alligator Lace	N/A																						
Flexco Plate/Rivet	#140/R5																																
Flexco Hinged	#375 or 550																																
Alligator Staple	N/A																																
Clipper Lace	N/A																																
Alligator Lace	N/A																																

**Special Characteristics:**

Medium oil resistant belt used to resist light traces of oils and terpenes. Widely used in the lumber, recycling and waste water industries. Can be used for some whole grains.

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*