Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB77f

Catalog #	**77f**
Item number:	**10502**
Description:	
3 Ply 330 3/16in x Bare MOR	
International Designation:	
N/A	

Construction:

Compound Top Cover	Black MOR
Color	Black
Top Cover Thickness (in)	(4.76 mm) 3/16 in
Top Cover Description	Smooth
Compound Bottom Cover	Poly/Nylon
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	3
Overall Gauge (in)	(9.65 mm) 3/8 in
Unit Weight- lb/PIW	0.1810 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black MOR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

Belt Strength:

Tension Rating (PIW)	330 PIW

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% Tension	18.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	16.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	12.00 in
Minimum Pulley Diameter- Tail	12.00 in

Splice Instructions:

Splice Step Size	8.00 in
Splice Process	Step Hot

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	#190/R5
Flexco Hinged	#550
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

Medium oil resistant belt used to resist light traces of oils and terpenes. Widely used in the lumber and recycling industries. Can be used for some whole grains. Ideal for slider bed applications.

*****All Values are nominal and subject to change without notice.*****