



# Michigan Industrial Belting Inc.

31617 Glendale St.  
Livonia, MI 48150

*We have years of experience and service under our belts.*

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

## MIB77g

<b>Catalog #</b>	<b>77g</b>
<b>Item number:</b>	<b>49524</b>
<b>Description:</b>	3 Ply 330 1/16in x Bare MOR
<b>International Designation:</b>	N/A

<b>Pulley Diameter, Minimum</b>	
Min. Pulley Dia. - Head @ 80 - 100% Tension	18.00 in
Min. Pulley Dia. - Head @ 60 - 79% Tension	16.00 in
Min. Pulley Dia. - Head @ 59% Tension or Below	12.00 in
Minimum Pulley Diameter- Tail	12.00 in

<b>Construction:</b>	
Compound Top Cover	Black MOR
Color	Black
Top Cover Thickness (in)	(1.59 mm) 1/16 in
Top Cover Description	Smooth
Compound Bottom Cover	Poly/Nylon
Bottom Cover Thickness (in)	(0.00 mm) 0.00 in
Bottom Cover Description	Bare
Number of Plies	3
Overall Gauge (in)	(5.59 mm) 7/32 in
Unit Weight- lb/PIW	0.1250 lbs/PIW
Carcass Type	Poly/Nylon
Compound	Black MOR
Temperature Range (°F)- High	225 °F
Temperature Range (°F)- Low	-25 °F

<b>Splice Instructions:</b>	
Splice Step Size	8.00 in
Splice Process	Step Hot

<b>Other:</b>	
Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

<b>Belt Strength:</b>	
Tension Rating (PIW)	330 PIW

<b>Suggested Fasteners:</b>	
Flexco Plate/Rivet	R2/R5
Flexco Hinged	N/A
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

<b>Special Characteristics:</b>
N/A

\*\*\*\*\*All Values are nominal and subject to change without notice.\*\*\*\*\*