



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

We have years of experience and service under our belts.

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

MIB79XT

Catalog # 79XT

Item number: 50232

Description:

3 Ply 170 7/16in Grey Diamond x Bare

International Designation:

TED300/3 PA50 SP213

Pulley Diameter, Minimum

Min. Pulley Dia. - Head @ 80 - 100% Tension 14.00 in

Min. Pulley Dia. - Head @ 60 - 79% Tension 12.00 in

Min. Pulley Dia. - Head @ 59% Tension or Below 8.00 in

Minimum Pulley Diameter- Tail 6.00 in

Construction:

Compound Top Cover Grey NR/BR

Color Gray

Top Cover Thickness (in) (11.00 mm) 27/64 in

Top Cover Description Grey 2" x 3" Diamond

Compound Bottom Cover None

Bottom Cover Thickness (in) (0.00 mm) 0.00 in

Bottom Cover Description Bare

Number of Plies 3

Overall Gauge (in) (14.99 mm) 37/64 in

Unit Weight- lb/PIW 0.3260 lbs/PIW

Carcass Type Polyester

Compound Black Grade 1

Temperature Range (°F)- High 200 °F

Temperature Range (°F)- Low -40 °F

Splice Instructions:

Splice Step Size 8.00 in

Splice Process Step Hot

Other:

Static Conducting No

Cross Rigid No

High Heat No

Impression Top Yes

Oil Resistant No

Fire Resistant No

FDA Approved No

Suggested Fasteners:

Flexco Plate/Rivet N/A

Flexco Hinged N/A

Alligator Staple #125

Clipper Lace #1

Alligator Lace #15

Belt Strength:

Tension Rating (PIW) 170 PIW

Special Characteristics:

Non-Marking. Good grip and abrasion resistance. Shore A 50 durometer maintains long-lasting grip for planer outfeed systems and light incline applications. Cold Temp -40C

*****All Values are nominal and subject to change without notice.*****