Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB86

Catalog #	**86**
Item number:	**10940**
Description:	
PVC 120 Black Roughtop x Brushed	
International Designation:	
N/A	

Construction:

Compound Top Cover	Black PVC
Color	Black
Top Cover Description	Roughtop
Compound Bottom Cover	Woven Poly
Bottom Cover Description	Brushed
Number of Plies	1
Overall Gauge (in)	(6.35 mm) 1/4 in
Unit Weight- lb/PIW	0.0900 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	Black PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	2.00 in

Belt Strength:

Tension Rating (PIW)	120 PIW

Splice Instructions:

Splice Step	No
Splice Finger	Yes

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	Yes
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#7

Special Characteristics:

Non-skid surface enables boxes and other products to be conveyed on incline or decline. Construction and compounds combine to provide best properties for high-traction conveying.

*****All Values are nominal and subject to change without notice.*****