



Michigan Industrial Belting Inc.

31617 Glendale St.
Livonia, MI 48150

We have years of experience and service under our belts.

Phone: 734-427-7700

Fax: 734-427-0788



Est 1978

MIB87

Catalog #	87
Item number:	10941
Description:	PVC 120 Green Supergrip Roughtop x Brushed
International Designation:	N/A

Pulley Diameter, Minimum	
Minimum Pulley Diameter	3.00 in

Belt Strength:	
Tension Rating (PIW)	120 PIW

Construction:	
Compound Top Cover	Green PVC
Color	Green
Top Cover Description	Roughtop
Compound Bottom Cover	Woven Poly
Bottom Cover Description	Brushed
Number of Plies	1
Overall Gauge (in)	(7.14 mm) 9/32 in
Unit Weight- lb/PIW	0.0900 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	Green PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Splice Instructions:	
Splice Step	No
Splice Finger	Yes

Other:	
Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	Yes
Oil Resistant	No
Fire Resistant	No
FDA Approved	No

Suggested Fasteners:	
Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#7

Special Characteristics:
 Non-skid surface enables boxes and other products to be conveyed on incline or decline. Construction and compounds combine to provide best properties for high-traction conveying. Green Supergrip is softer durometer for highest grab and steepest inclines.

*****All Values are nominal and subject to change without notice.*****