Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB95

Catalog #	**95**
Item number:	**10908**
Description:	
PVC 150 Blk FS x Brushed FR	
International Designation:	
N/A	

Construction:

Compound Top Cover	Woven Poly
Color	Black
Top Cover Description	Friction Surface
Compound Bottom Cover	Woven Poly
Bottom Cover Description	Brushed
Number of Plies	1
Overall Gauge (in)	(3.00 mm) 7/64 in
Unit Weight- lb/PIW	0.0560 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	Black PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum

Minimum Pulley Diameter	3.00 in

Belt Strength:

Tension Rating (PIW)	150 PIW

Splice Instructions:

Splice Step	No
Splice Finger	Yes

Other:

Static Conducting	No
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	Yes
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	N/A
Flexco Hinged	N/A
Alligator Staple	#125
Clipper Lace	#1
Alligator Lace	#15

Special Characteristics:

Has proven to be the longest wearing, best performing, most problem free package handling belt available today. Economical, general purpose specifications ideal for a variety of slider bed, applications. Offer low stretch, high fastener holding ability and superior rip, tear, and gouge resistance

*****All Values are nominal and subject to change without notice.*****