Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

We have years of experience and service under our belts.

MIB96

Catalog # 96
Item number: 10912
Description:
PVC 200 Blk C x C SC/FR
International Designation:
N/A

Construction:

Compound Top Cover	Black PVC
Color	Black
Top Cover Description	Smooth
Compound Bottom Cover	Black PVC
Bottom Cover Description	Smooth
Number of Plies	1
Overall Gauge (in)	(6.00 mm) 15/64 in
Unit Weight- lb/PIW	0.1190 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	Black PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum:

Minimum Pulley Diameter Conveyor	4.00 in
Minimum Pulley Diameter Elevator	8.00 in

Bucket Projection, Maximum:

Maximum Bucket Projection Grain	6.00 in
Maximum Bucket Projection Industrial	6.00 in

Belt Strength:

Tension Rating Conveyor (PIW)	200 PIW
Tension Rating Elevator (PIW) Allowable	200 PIW
Tension Rating Elevator (PIW) Preferred	185 PIW

Other:

Static Conducting	Yes
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	Yes
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	R5
Flexco Hinged	#375
Alligator Staple	#187
Clipper Lace	#4-1/2
Alligator Lace	#27

Special Characteristics:

The most common, best performance yield elevator belting available in the feed and grain industry. Features low stretch; trouble-free operation; high bolt-holding ability; and resistance to grain oils. Also static conductive and flame resistant. Dura-Splice and Maxi-Splice recommended for bucket elevator applications. Service factor of 10:1

*****All Values are nominal and subject to change without notice.*****