Michigan Industrial Belting Inc.
31617 Glendale St.
Livonia, MI 48150
We have years of experience and service under our belts.

Phone: 734-427-7700
Fax: 734-427-0788
Est 1978

MIB99

Catalog #	**99**
Item number:	**10922**
Description:	
PVC 350 Blk C x C SC/FR	
International Designation:	
N/A	

Construction:

Compound Top Cover	Black PVC
Color	Black
Top Cover Description	Smooth
Compound Bottom Cover	Black PVC
Bottom Cover Description	Smooth
Number of Plies	1
Overall Gauge (in)	(7.60 mm) 19/64 in
Unit Weight- lb/PIW	0.1600 lbs/PIW
Carcass Type	Interwoven Polyester
Compound	Black PVC
Temperature Range (°F)- High	180 °F
Temperature Range (°F)- Low	0 °F

Pulley Diameter, Minimum:

Minimum Pulley Diameter Conveyor	8.00 in
Minimum Pulley Diameter Elevator	12.00 in

Bucket Projection, Maximum:

Maximum Bucket Projection Grain	7.00 in
Maximum Bucket Projection Industrial	8.00 in

Belt Strength:

Tension Rating Conveyor (PIW)	350 PIW
Tension Rating Elevator (PIW) Allowable	350 PIW
Tension Rating Elevator (PIW) Preferred	280 PIW

Other:

Static Conducting	Yes
Cross Rigid	No
High Heat	No
Impression Top	No
Oil Resistant	Yes
Fire Resistant	Yes
FDA Approved	No

Suggested Fasteners:

Flexco Plate/Rivet	R5
Flexco Hinged	#550
Alligator Staple	N/A
Clipper Lace	N/A
Alligator Lace	N/A

Special Characteristics:

The most common, best performance yield elevator belting available in the feed and grain industry. Features low stretch; trouble-free operation; high bolt-holding ability; and resistance to grain oils. Also static conductive and flame resistant.Dura-Splice and Maxi-Splice recommended for bucket elevator applications.

*****All Values are nominal and subject to change without notice.*****